



# Accelerotor Viewer

The VeriVide Accelerotor Viewer provides standardized viewing conditions for the grading of samples to various standards. Designed for the evaluation of samples that have been through the suggested AATCC Accelerotor tests, the Viewer allows you to grade abrasion and scuffing under controlled, lighting conditions, by providing a constant, flicker free, and even illumination via transmitted light.



## Specifications - Order code: ACCEL

LIGHT SOURCE		VOLTAGE	
TL84		230v	110v

SIZE (MM)	WIDTH	HEIGHT	DEPTH
OVERALL	350	170	240

The Accelerotor Viewer is supplied with interchangeable masks to increase it's flexibility, conforming to a wide range of standards and applications. Masks can also be supplied in specific sizes and shapes for individual customer needs, to a maximum size of 260mm x 135mm.

**Also conforming to: AATCC 93. ASTM D1175. M&S P26. NEXT TM31**

The Accelerator Abrasion Resistance is sold as a complete unit however, if you have your own specifications a tailored unit can be made.

For more information please contact our Sales Department or E-mail us at [enquiries@verivide.com](mailto:enquiries@verivide.com)

VeriVide is committed to innovation in colour assessment and quality control. From constructing bespoke standardised viewing environments to developing new lighting products to meet industry standards, improving your quality and productivity is always our priority.



For further technical information visit: [www.verivide.com](http://www.verivide.com)



Scan the QR code on your mobile device to go directly to our website

Tel: +44 (0)116 284 7790  
Email: [sales@verivide.com](mailto:sales@verivide.com)

VeriVide Limited, Quartz Close, Warrens Business Park, Enderby, Leicester LE19 4SG UK